

# EasyTrak™ Premium PTZ

## SC-P36P / SC-P36N

## NUVICO®



### KEY FEATURES

- Modular Design
- GUI (Graphical User Interface)
- 99 Schedule management through real time clock
- Auto Calibration by magnetic sensor
- Auto Tracking
- Individually programmable preset control
- De-icing Housing (Optional)
- Day & Night Schedule & Modular Design improvement from SD Series
- Remote Heater Control

### CONSTRUCTION

- 6" Polycarbonate Bubble
- Impact Resistant Dome w/ Aluminum, Pendant Housing w/ Wall Mount
- Weatherproof - IP66
- Fan & Heater (Optional)

### AVAILABLE MODELS

- SC-P36P-PHW • SC-P35P-PHW
- SC-P36N-PHW • SC-P35N-PHW
- SC-P36P-IHW • SC-P35P-IHW
- SC-P36N-IHW • SC-P35N-IHW
- SC-P36P-FMH • SC-P35P-FMH
- SC-P36N-FMH • SC-P35N-FMH
- SC-P36P-SMH • SC-P35P-SMH
- SC-P36N-SMH • SC-P35N-SMH

### AVAILABLE ACCESSORIES

- SC-SMH: Surface Mount Housing Kit
- SC-FMH: Flush Mount Housing Kit
- SC-OH: Outdoor Housing
- SC-IH: Indoor Housing
- SC-FH: Fan & Heater
- SC-BS: Base
- CA-JB2: Power Box
- SD-PMB: Pole Mount Bracket
- SD-CMB: Corner Mount Bracket
- SD-PM: Pedestal Mount
- SD-PPM: Parapet Mount
- SD-IMB: I-Beam Mount Bracket
- SD-WL: Wall Mount Bracket

### TECHNICAL SPECIFICATIONS

Technical Specifications	SC-P36P	SC-P36N
Video Format	PAL	NTSC
Image Sensor	1/4" Sony EXview HAD CCD	
Horizontal Resolution	550 TV Lines	
Day/Night Functionality	Yes w/ ICR	
Lens Type	36X A/F Optical Zoom 3.4-122.4mm	
Digital Zoom	12X Digital Zoom	
Angle of View	57.8°(W) ~ 1.7°(T)	
Min. Focus Distance	30cm	
Communication	RS-485	
Sync System	Internal	
Effective Pixels (HxV)	752(H) x 582(V)	768(H) x 494(V)
Electronic Shutter	1/1 ~ 1/10,000 sec.	
Main Video Output	1.0 Vp-p Composite, 75 ohm	
Minimum Illumination	1.4 Lux (Color), 0.01 Lux (ICR/DSS:On)	
S/N Ratio	More than 50dB (AGC Off)	
WDR	Yes	
BLC	Yes (On/Off)	
DNR	Yes	
Focus / WB / Iris / Gain Control	Auto with Manual Override	
Pan Travel Range	360° Continuous	
Manual Pan Speed	0.1° ~ 105°/sec	
Manual Turbo Pan Speed	420°/sec	
Preset Pan Speed	420°/sec	
Tilt Travel Range	-5° ~ 185°	
Manual Tilt Speed	0.1° ~ 105°/sec	
Preset Tilt Speed	420°/sec	
Proportional Pan & Tilt	Yes	
Preset Accuracy	0.2°	
Preset	248 Positions	
Area Title	24	
Privacy Zone	8	
Title Character	16	
Tour	8	
Pattern	8 (480 seconds)	
Auto Pan	16 Scan, 1 Auto Pan	
Automatic Flip (180°)	Instant Digital Flip	
Alarm Input / Output	8 / 2	
<b>General Information</b>	<b>SC-P36P</b>	<b>SC-P36N</b>
Operating Temperature	0°C~+50°C (Normal) -40°C~+55°C (Fan&Heater)	
Operating Humidity	Within 90% RH	
<b>Power Requirement</b>	<b>SC-P36P</b>	<b>SC-P36N</b>
Dome Only	24VAC / 20W	
w/ Fan & Normal Heater	24VAC / 50W	
De-Icing Heater	24VAC / 160W	

\*specifications are subject to change without any prior notice.

### DIMENSIONS

Unit: Inches (mm)

